## (19) World Intellectual Property Organization International Bureau





(43) International Publication Date 21 May 2004 (21.05.2004)

## **PCT**

## (10) International Publication Number WO 2004/043086 A2

(51) International Patent Classification7:

H04Q 7/00

(21) International Application Number:

PCT/SE2003/001708

(22) International Filing Date:

5 November 2003 (05.11.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/423,600

5 November 2002 (05.11.2002) U

- (71) Applicant (for all designated States except US): TELE-FONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): WALLENTIN, Pontus [SE/SE]; Hjälmsätersgatan 2B, S-582 17 Linköping (SE).
- (74) Agent: MAGNUSSON, Monica; c/o ERicsson AB, Patent Unit Radio Networks, S-164 80 Stockholm (SE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: COLLECTIVE NOTIFICATION OF NODE RESET TO SUBSET OF CONNECTIONS IN RADIO ACCESS NETWORK

(ST) Abstract: Upon reset of a control node (261) of a radio access network (24) which controls connections with user equipment units (30) in a connected mode, a message (102) indicative of the reset is sent between nodes of the radio access network. The message results from occurrence of a reset procedure (104) affecting the control node. The message includes an element which collectively indicates that a subset of the connections (i.e., not all of the connections) controlled by the control node are to be released. Inclusion in the message of the element, also known as the subset reset element, facilitates return to an idle mode of the user equipment units involved in the subset of the connections. By virtue of inclusion of the subset reset element, the message need not go to one extreme of listing individually each of the connections affected by the reset, nor to another extreme of specifying all connections controlled by the control node.